



Quality Products. Service Excellence.

Datawind Filterfans *DPF Series*

Type 12

NEW



Features

- Maintains a UL Tested NEMA Type 12 seal against enclosure
- Externally mounted for space restricted installations such as control panels and IT equipment racks
- 30 degree slope top housing to avoid dust collection
- IEC power connector 6 foot long cable - NEMA 5-15P (115V) and IEC C14 (230V)
- Thermostat with 13 foot long cable allows for placement near heat sensitive locations
- Maintenance LED indication light shows filter status
- Plastic components made from strong, heat resistant (ABS-FR), UL94-V0 fire approved material
- Fluted filter-mat provides longer service life, holding more dust before impeding airflow extending the mean time between maintenance; especially critical for those located in less accessible areas
- Metal housing offered in White (RAL 9003) and Black (RAL 9004) with complementary plastic fan grill
- NOTE - Datawind fan packages pressurize cabinets (push air in) so an exhaust location is needed as a path for heat to escape the cabinet. See table below for exhaust filter option:

Accessories

- Replacement Filters
- Thermostats

Part Number	Part Number	Free Flow	Exhaust Filter	Exhaust Filter				
White RAL9003	Black RAL9004	Voltage	Light Gray RAL7035	Black RAL9011				
		CFM	H	W	D			
DPF22000A115WH	DPF22000A115BK	115 VAC	38	9.40	6.80	2.76	PFA20000LG	PFA20000BK
DPF22000A230WH	DPF22000A230BK	230 VAC	38	9.40	6.80	2.76	PFA20000LG	PFA20000BK
DPF33000A115WH	DPF33000A115BK	115 VAC	152	11.90	9.30	3.30	PFA30000LG	PFA30000BK
DPF33000A230WH	DPF33000A230BK	230 VAC	152	11.90	9.30	3.30	PFA30000LG	PFA30000BK
DPF67000A115WH	DPF67000A115BK	115 VAC	560	17.50	14.90	5.50	PFA60000LG	PFA60000BK
DPF67000A230WH	DPF67000A230BK	230 VAC	560	17.50	14.90	5.50	PFA60000LG	PFA60000BK

Tags: filterfan, filter, datawind, NEMA 12, Type 12, dust, rack, IT, control panel, thermostat, pressurize *Data subject to change without notice*

