

OptiTap® 1F Single-Tube, OptiTap to stub end, Toneable, Gel-Filled Cable Assembly Single-mode (OS2), 1000 ft



Part Number:
004301EB1TDA00F-P

As an industry leader in optical connectivity products, Corning designs and manufactures the SST-Drop™ cable assembly with factory-terminated, environmentally sealed and hardened connectors to reduce the cost and the time of drop cable deployment in optical access networks. The OptiTap® single-fiber drop cable assembly is specifically designed to significantly reduce required drop cable installation.

Features and Benefits

Smaller profile and reduced bend-radius

Designed for rapid connection to external flush-mounted bulkhead adapters on terminals or closures

Robust design keeps connector intact during installation

Integral pulling eye/connector cap designed for 100 lb maximum pulling tension



OptiTap® 1F Single-Tube, OptiTap to stub end, Toneable, Gel-Filled Cable Assembly Single-mode (OS2), 1000 ft



Specifications

General Specifications	
Fiber Category	Single-mode (OS2)
Cable Assembly Type	Drop Assemblies
Application	Direct Buried, Aerial, Duct
Packaging	Individual Pack
Termination	One end

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	SST-Drop™ cable fully compliant with Telcordia GR-20 requirements
Design and Test Criteria	Telcordia GR-3120

Environmental Conditions	
Temperature Range, Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Design	
Fiber Count	1
Fiber Type	Single-mode

Mechanical Specifications	
Cold Mate/Demate	-40 °C (-40 °F)
Axial Pull, Plug to Cable, Through the Dust Cap	100 lb in axial pull with load applied to the dust cap
Axial Pull Plug to Adapter Coupling Strength	50 lbs

OptiTap® 1F Single-Tube, OptiTap to stub end, Toneable, Gel-Filled Cable Assembly Single-mode (OS2), 1000 ft



Optical Characteristics	
Fiber Code	E
Fiber Name	Single-mode (OS2)
Fiber Type	Single-mode (OS2) / 250 µm
Fiber Compliance	ITU-T G.652.D
Performance Option Code	01
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Category	OS2

Specifications - Connector A	
Reflectance, Typical	-65 dB
Insertion Loss, Typical	≤ 0.15 dB
Connector Type	No connector

Specifications - Connector B	
Reflectance, Typical	-65 dB
Insertion Loss, Typical	≤ 0.15 dB
Connector Type	SC APC OptiTap® Connector

Dimensions	
Length	1000 ft
Weight	9.3 kg

Ordering Information	
Product Number	004301EB1TDA00F-P
EAN Code	4056418758404
Packaging Method	Reel

OptiTap® 1F Single-Tube, OptiTap to stub end, Toneable, Gel-Filled Cable Assembly Single-mode (OS2), 1000 ft



Ordering Information	
Units per Delivery	1/1
Shipping Height	838 mm (32.99 in)
Shipping Width	178 mm (7.01 in)
Shipping Depth	838 mm (32.99 in)



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.