

GPPO Male Surface Mount Coplanar, Smooth Bore, 0.108 Length

CORNING

Part Number:
B012-P95-02

Features and Benefits

Designed to accommodate both radial and axial misalignment with negligible voltage standing wave ratio (VSWR) change

Meets all MIL-STD Performance specifications

Center-to-center spacing of 0.140-in available for increased package density

Frequency from DC to 65 GHz



GPPO Male Surface Mount Coplanar, Smooth Bore, 0.108 Length



Specifications

General Specifications	
Finish, Contacts	Gold plated per MIL-G-45204, Type I, Grade C, Class 1, Over Nickel Plate per SAE AMS-QQ-N-290
Materials, Outer Contacts	Beryllium Copper per ASTM B196 and or/ASTM B197
Materials, Springs	17-7 Stainless Steel per ASTM A313-95A
Finish, Bodies	Gold plated per MIL-G-45204, Type I, Grade C, Class 1, Over Nickel Plate per SAE AMS-QQ-N-290
Materials, Center Contacts	Beryllium Copper per ASTM B196 and or/ASTM B197
Impedance	50 Ω
Materials, Insulators	PTFE Fluorocarbon per ASTM D1710
Frequency Range	DC to 65 GHz typ.
Materials, Bodies	Beryllium Copper per ASTM B196 and or/ASTM B197
Product Type	Surface Mounts

Design	
Leg Length	0.075 in
Diameter B	0.508 mm (0.02 in)

Mechanical Specifications	
Tolerated Misalignment Axial	0.010 (flush to 0.010 from reference plane)
Tolerated Misalignment Radial	± 0.010
Typical Force to Engage / Disengage FD	4.5 lbs / 6.5 lbs
Typical Force to Engage / Disengage SB	2.5 lbs / 1.5 lbs

Electrical Specifications	
VSWR	1.20:1 to 20 GHz
Insertion Loss	04 \sqrt{f} (GHz)
Contact Resistance - Inner Conductor	6 m Ω

GPPO Male Surface Mount Coplanar, Smooth Bore, 0.108 Length



Electrical Specifications	
Contact Resistance - Outer Conductor	2 mΩ
Insulation Resistance	5,000 megohms minimum
DWV at Sea Level	325 Vrms
RF Leakage	-80 dB to 3 GHz, -65 dB to 26.5 GHz



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.