

Evolv® Terminal with Pushlok® Technology 8 port, preconnectorized OptiTip® stub, SST Dielectric, 100 ft

CORNING

Part Number:
DFA8F1FDD1M1100F0P

Pushlok® hardened connector technology is the key component enabling smaller terminals for FTTx networks than ever before. Designed for use in nearly every access network environment, the terminal is small enough to be placed in existing handholes or pedestals where space is paramount, on building facades, or in aerial networks (pole- or strand-mount). Improved aesthetics improve end-user adoption for facade applications. There are two styles of terminals designed to meet various space and density requirements: terminals with one row of adapter ports and terminals with two rows of adapter ports. For terminals with one row of adapter ports, the ports are aligned in a single row with the input stub on the left and 2-, 4-, 6- or 8-distribution ports on the right. For terminals with two rows of ports, the input stub is on the front left of the terminal and there are 6-, 8-, 12- or 16- distribution ports. Each port's corresponding release button is actuated to remove the dust cap or drop. When installing drops, the keyed ports provide an audible and physical positive feedback minimizing technician variation and potential damage due to mishandling.

Features and Benefits

Pushlok™ cable assembly connector ports for customer drop terminations

Lower installation cost and increased speed of connection

Standard and integrated splitter terminal options

Durability

Solution supports various architecture types

Durability

100 lb cable tensile strength

Available stubbed or preterminated with OptiTip® multifiber connector technology

Compatible with existing FlexNAP™ installations

Small form factor optimizes space in pedestals/handholes

Lower profile overall with drop entry ports on bottom

Ultrasonically welded housing

Eliminates water ingress potential and prevents unwanted entry in the field

Factory-terminated polished connectors

Eliminates loss associated with excess fusion splices



Evolv® Terminal with Pushlok® Technology, 8 port, preconnectorized OptiTip® stub, SST Dielectric, 100 ft

Evolv® Terminal with Pushlok® Technology 8 port, preconnectorized OptiTip® stub, SST Dielectric, 100 ft

CORNING

Specifications

| General Specifications | |
|-------------------------------------|--|
| Product Type | Terminals |
| Environment | Outdoor |
| Cable Type | SST Flat Dielectric Drop |
| Fiber Category | ITU-TG.652.D (OS2) |
| Packaging | Individual Pack |
| Preconnectorized "Stubbed" Hardware | Yes |
| Lockable | No |
| Cable type stubbed | SST Drop Cable |
| Mounting Type | Strand mount, Pole-mount, Pedestal mount, Handhole Mount |
| Splice option | No |
| Application | FTTx |
| Technology | Pushlok® |

| Standards | |
|--------------------------|---|
| RoHS | Free of hazardous substances according to RoHS 2011/65/EU |
| Design and Test Criteria | IP68 |

| Environmental Conditions | |
|------------------------------|-------------------------------------|
| Temperature Range, Operation | -40 °C to 85 °C (-40 °F to 185 °F) |
| Temperature Range, Storage | -40 °C to 85 °C (-40 °F to 185 °F) |

| Design | |
|-------------------|--|
| Fiber Count | 8 |
| Input Fiber Count | 8 |
| Fiber Coloring | Blue, Orange, Green, Brown, Slate, White, Red, Black |

Evolv® Terminal with Pushlok® Technology 8 port, preconnectorized OptiTip® stub, SST Dielectric, 100 ft

CORNING

Design

| | |
|--|--------------------------|
| Fibers per Port | 1 |
| Number of single-fiber ports, SC APC connector | 8 |
| Housing Material | Plastic |
| Pigtail Length | 100 ft |
| Input Cable Type | SST Flat Dielectric Drop |
| Locking Availability | No |
| Sealing Type | Welded |
| Housing Color | Black |
| Number of Fibers in Input Cable | 8 |
| Number of Ports | 8 |

Design - Adapter

| | |
|--------------|----------|
| Adapter Type | Pushlok® |
|--------------|----------|

Mechanical Specifications

| | |
|------------------|-----------------|
| Cold Mate/Demate | -40 °C (-40 °F) |
| Cable Length | 100 ft |

Optical Specification - Hardware

| | |
|----------------------------|--------|
| Module Insertion Loss, Max | 0.5 dB |
| Reflectance, Maximum | 65 dB |

Connector Specs

| | |
|--------|-----|
| Polish | APC |
|--------|-----|

Evolv® Terminal with Pushlok® Technology 8 port, preconnectorized OptiTip® stub, SST Dielectric, 100 ft

CORNING

Specifications - Connector A

| | |
|-------------------------|-----------|
| Connector Type | Pushlok® |
| Housing Color | Black |
| Polish | APC |
| Housing Material | Plastic |
| Endface Type | APC |
| Insertion Loss, Max. | 0.5 dB |
| Insertion Loss, Typical | ≤ 0.15 dB |

Specifications - Connector B

| | |
|----------------------|----------|
| Connector Type | Pushlok® |
| Housing Color | Black |
| Polish | APC |
| Housing Material | Plastic |
| Insertion Loss, Max. | 0.5 dB |

Dimensions

| | |
|--------|------------------|
| Length | 100 ft |
| Height | 30 mm (1.18 in) |
| Width | 134 mm (5.28 in) |
| Depth | 152 mm (5.98 in) |
| Weight | 1.86 kg |

Ordering Information

| | |
|--------------------|--------------------|
| Product Number | DFA8F1FDD1M1100F0P |
| Packaging Method | Box |
| Shipping Weight | 1.86 kg |
| Units per Delivery | 1/1 |
| Shipping Height | 762 mm (30 in) |

**Evolv® Terminal with Pushlok® Technology 8
port, preconnectorized OptiTip® stub, SST
Dielectric, 100 ft**



| Ordering Information | |
|----------------------|------------------|
| Shipping Width | 762 mm (30 in) |
| Shipping Depth | 152 mm (5.98 in) |



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.