#### **Universal Routing Kit for 24F Loose Tube Cable**



## Part Number: FUR-24F

12-fibers for fusion splicing or direct termination. The universal routing kits are available with two 12-fiber (FUR-24F) or three 12-fiber. Corning's universal routing kits are specifically designed for the routing of 24-fiber buffer tubes to 12-fiber tubes.

These universal routing kits provide the ultimate solution for those users who want to route 24-fiber tubes down to FUR-36F) units in lengths of 1.5 m (59 in).

#### **Features and Benefits**

Reducing complexity
24 Fiber break out to 12 Fiber

**Snap-together furcation** Eliminates epoxy

Fiber routing capabilities
Fusion Splicing
Direct Termination





# **Universal Routing Kit for 24F Loose Tube Cable**



## Specifications

General Specifications	
Environment	Indoor
Product Type	Fan-out Kits
Fanout Type	Routing Kit
Cable Type	ALTOS HD and MiniXtend Loose Tube Cables

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

<b>Environmental Conditions</b>	
Temperature Range, Operation	-40 °C to 70 °C (-40 °F to 158 °F )

Design	
Fan-Out Tubing Color	Clear
Fiber Count	24
Fibers per Buffer Tube	24

Mechanical Specifications - Fan-Out Kit	
Furcation Length	59 in
Tubing Length	1499 mm (59.02 in)

Ordering Information	
Product Number	FUR-24F
Package Contents	Fan-out top, fan-out bottom, fan-out tubing
Units per Delivery	1/1

### **Universal Routing Kit for 24F Loose Tube Cable**





Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • <a href="www.corning.com/opcomm">www.corning.com/opcomm</a>

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.