

SPN064-15TL

SPN064-15TL Part Number: Category: Basic Sub Category: Surge Power Configuration: 15A, 120V, 1.4kW Physical Configuration:

19 in / 483 mm, Horizontal



Description:	SPN064-15TL comes equipped with built-in surge protection. This basic power distribution unit is ideal for environments lacking facility-level surge suppression or for applications requiring additional protection.	
Product Summary:	SPN064-15TL - Basic, Surge, 15A, 120V, Horizontal, (6) NEMA 5-15R, breakered, 15 ft power cord with L5- 15P, Black Powder Coat.	
Plug Form:	Receptacle: NEMA 5-15R (Quantity: 6)	
Chassis Colors Options:		

To discuss color options, contact your local sales representative.

Geist Americas

Geist Europe

Geist Asia

SPN064-15TL



Product Specification and Options:

Quantity Of Inputs	1
Voltage	120V
Current	15A
VA per Input (Load Capacity)	1.4kW
Frequency	50/60 Hz
Over Current Protection	15A Thermal Breaker
Switch	No
Indicators - LED(s)	1 - Power ON Green LED
Power Cable Wire Gauge	14/3
Power Cable Length	15ft
Plug Type	NEMA L5-15P Twistlock
Receptacle/Socket Type #1	NEMA 5-15R
- Quantity on Rear	6
- Quantity per Breaker	6
- Style	Duplex
- Maximum Output per Receptacle/Socket	15A
- Voltage per Receptacle/Socket	120V
Joule Rating	720
Maximum Clamping Voltage	340V
Response Time	< 5 nanoseconds
Technology Used	Super MOVS
Surge Indicator Red LED	Yes
Continuous Operating Temperature Range	10-45C / 50-113F
Heavy Steel - Powder Coat Finish	Black
Configuration	19 in / 435 mm Horizontal Rackmount
Flush Mount	Yes
Made in the USA	Yes
Product Warranty	Lifetime (Surge Suppression - 10 Years)
Connected Equipment Warranty	Ten Year - \$10000
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	UL & c-UL Listed 60950
Chassis Dimensions (HxWxD)	1.72in x 17in x 3.75in
Shipped Weight	6lbs (2.72kg)

Geist Americas

800.432.3219 qeistalobal.com

1.877.449.4150 geistglobal.com

Geist Europe

+44 (0) 1823.275100 geistglobal.com

Geist Asia

China +86.755.86639505 geistglobal.com