



Product: <u>DAUP</u> ☑

Category 6A Cable, 4 Pair, U/UTP, CMP

Product Description

Category 6A Premise Horizontal Cable, 4 Pair, 23 AWG Solid Bare Copper Conductors, U/UTP, Plenum-CMP, Flamarrest® PVC-LS Jacket

Technical Specifications

Product Overview

| Suitable Applications: | Premise Horizontal Cable, Ethernet 10GBASE-T |
|------------------------|--|

Construction Details

Conductor

| Size | Stranding | Material | No. of Pairs |
|--------|-----------|------------------|--------------|
| 23 AWG | Solid | BC - Bare Copper | 4 |

Insulation

| Material | Color Code |
|--------------------------------------|--|
| FEP - Fluorinated Ethylene Propylene | White & Blue, White & Orange, White & Green, White & Brown |

Outer Jacket

| | Sep | parator | Material | Material Trade Name | Nom. Diameter | Ripcord |
|---------------------------------|----------------|-------------------------------------|--------------------------|---------------------|--------------------|---------|
| Center Member (Pate | tented X-Splir | ne®), EquiBlock™ Barrier Technology | PVC - Polyvinyl Chloride | Flamarrest® | 0.250 in (6.35 mm) | Yes |
| Overall Cable Diamet (Nominal): | eter | 0.250 in (6.35 mm) | | | | |

Electrical Characteristics

Electricals

| Max. Conductor DCR | Max. Capacitance Unbalance |
|---------------------------|----------------------------|
| 82 Ohm/km (25 Ohm/1000ft) | 45 pF/100m |

Delay

| Frequency | Max. Delay | Max. Delay Skew | Nom. Velocity of Prop. |
|-----------|---------------|-----------------|------------------------|
| 100 MHz | 537.6 ns/100m | 45 ns/100m | 69% |

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

| UL Temperature | Operating | Storage |
|----------------|----------------|----------------|
| 75°C | -20°C To +75°C | -20°C To +75°C |

Bend Radius

Stationary Min. 1 in (25 mm)

| Max. Pull Tension: | 25 lbs (11 kg) |
|--------------------|--------------------------|
| Bulk Cable Weight: | 34 lbs/1000ft (51 kg/km) |

Standards and Compliance

| F : | |
|---------------------------------------|---|
| Environmental Suitability: | Plenum, Indoor |
| Flammability / Reaction to Fire: | NFPA 262, UL 910 (Plenum), FT6 |
| NEC / UL Compliance: | Article 800 |
| CEC / C(UL) Compliance: | CMP |
| ICEA Compliance: | S-116-732 |
| IEEE Compliance: | IEEE 802.3bt Type 1, Type 2, Type 3, Type 4 |
| NEMA Compliance: | ANSI/NEMA WC-66 |
| Data Category: | Category 6A |
| TIA/EIA Compliance: | ANSI/TIA-568.2-D Category 6A |
| Third Party Performance Verification: | Channel/Category 6A |
| ISO/IEC Compliance: | ISO/IEC 11801-1, IEC 61156-5 |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16 |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Non-Plenum Number: | DAUR |

Product Notes

| Notes: | Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0. | 1 |
|--------|---|---|
|--------|---|---|

History

| Update and Revision: | Revision Number: 0.125 Revision Date: 06-04-2025 |
|----------------------|--|
| ' | |

Part Numbers

Variants

| Item # | Color | Putup Type | Length |
|--------------|-------------|------------|----------|
| DAUP 0101000 | Black | Reel | 1,000 ft |
| DAUP D151000 | Blue | Reel | 1,000 ft |
| DAUP 0081000 | Gray | Reel | 1,000 ft |
| DAUP 0051000 | Green, Dark | Reel | 1,000 ft |
| DAUP 0031000 | Orange | Reel | 1,000 ft |
| DAUP 0021000 | Red | Reel | 1,000 ft |
| DAUP 0091000 | White | Reel | 1,000 ft |
| DAUP 0041000 | Yellow | Reel | 1,000 ft |

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.