

LDF6RK-50



LDF6-50, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1-1/4 in, black non-halogenated, fire retardant polyolefin jacket

OBSOLETE

Replaced By:

AVA6RK-50	AVA6RK-50, HELIAX® Andrew Virtual Air™ Coaxial Cable, corrugated copper, 1-1/4 in, black , fire retardant polyolefin jacket B2ca- s1a, d2,a1 (CPR testing is conducted annually please reference the website for latest classification)
AVA6RKD-50	AVA6-50, HELIAX® Andrew Virtual Air™ Coaxial Cable, corrugated copper, 1-1/4 in, black , fire retardant polyolefin jacket

Product Classification

Product Type	Coaxial wireless cable
Product Brand	HELIAX®
Product Series	LDF6-50

General Specifications

Flexibility	Standard
Jacket Color	Black
Performance Note	Attenuation values typical, guaranteed within 5%

Dimensions

Diameter Over Dielectric	33.782 mm 1.33 in
Diameter Over Jacket	39.37 mm 1.55 in
Inner Conductor OD	13.208 mm 0.52 in
Outer Conductor OD	35.814 mm 1.41 in
Nominal Size	1-1/4 in

Electrical Specifications

LDF6RK-50

Cable Impedance	50 ohm $\pm$ 1 ohm
Capacitance	75.1 pF/m 22.89 pF/ft
dc Resistance, Inner Conductor	0.722 ohms/km 0.22 ohms/kft
dc Resistance, Outer Conductor	0.623 ohms/km 0.19 ohms/kft
dc Test Voltage	9000 V
Inductance	0.184 μ H/m 0.056 μ H/ft
Insulation Resistance	100000 MOhms-km
Jacket Spark Test Voltage (rms)	8000 V
Operating Frequency Band	1 – 3300 MHz
Peak Power	205 kW
Velocity	89 %

Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Average Power (kW)
1.0	0.075	0.023	127.47
1.5	0.092	0.028	103.94
2.0	0.107	0.033	89.92
10.0	0.241	0.074	39.81
20.0	0.344	0.105	27.94
30.0	0.423	0.129	22.69
50.0	0.551	0.168	17.42
85.0	0.728	0.222	13.2
88.0	0.741	0.226	12.96
100.0	0.792	0.242	12.12
108.0	0.825	0.252	11.64
150.0	0.983	0.299	9.77
174.0	1.064	0.324	9.03
200.0	1.146	0.349	8.38
204.0	1.158	0.353	8.29
300.0	1.428	0.435	6.73
400.0	1.672	0.51	5.74
450.0	1.784	0.544	5.38
460.0	1.806	0.551	5.32
500.0	1.892	0.577	5.08

LDF6RK-50

512.0	1.917	0.584	5.01
600.0	2.095	0.639	4.58
700.0	2.286	0.697	4.2
800.0	2.466	0.752	3.89
824.0	2.508	0.764	3.83
894.0	2.628	0.801	3.65
960.0	2.738	0.834	3.51
1000.0	2.803	0.854	3.43
1218.0	3.143	0.958	3.06
1250.0	3.191	0.973	3.01
1500.0	3.553	1.083	2.7
1700.0	3.827	1.166	2.51
1794.0	3.952	1.204	2.43
1800.0	3.96	1.207	2.43
2000.0	4.219	1.286	2.28
2100.0	4.345	1.324	2.21
2200.0	4.469	1.362	2.15
2300.0	4.591	1.399	2.09
2500.0	4.831	1.472	1.99
2700.0	5.065	1.544	1.9
3000.0	5.406	1.648	1.78

Material Specifications

Dielectric Material	Foam PE
Jacket Material	Non-halogenated, fire retardant polyolefin
Inner Conductor Material	Copper tube
Outer Conductor Material	Corrugated copper

Mechanical Specifications

Minimum Bend Radius, multiple Bends	381 mm 15 in
Minimum Bend Radius, single Bend	152.4 mm 6 in
Number of Bends, minimum	15
Number of Bends, typical	40
Tensile Strength	590 kg 1,300.726 lb
Bending Moment	48.8 N-m 431.916 in lb

LDF6RK-50

Flat Plate Crush Strength

2.2 kg/mm | 123.194 lb/in

Environmental Specifications

Installation temperature	-25 °C to +60 °C (-13 °F to +140 °F)
Operating Temperature	-30 °C to +80 °C (-22 °F to +176 °F)
Storage Temperature	-30 °C to +80 °C (-22 °F to +176 °F)
Attenuation, Ambient Temperature	68 °F 20 °C
Average Power, Ambient Temperature	104 °F 40 °C
Average Power, Inner Conductor Temperature	212 °F 100 °C
Fire Retardancy Test Method	UL 1666/CATVR
Smoke Index Test Method	IEC 61034
Toxicity Index Test Method	IEC 60754-1 IEC 60754-2

Packaging and Weights

Cable weight

1.02 kg/m | 0.685 lb/ft

Regulatory Compliance/Certifications

Agency	Classification
UL/ETL Certification	CATVR

