


# SRC1-U3B2A1BC000



NOVUX™ Specialty Range Closure 50, splice/patch, 2x SC/APC adapter, 2x SC/APC Grade B 900µm pigtail, no splitters, 6 splices, SMOUV® 45mm splice protectors, black, no splitter, 2x NVX-CR-MC-RD-NN cable retentionS

- Modern drop solution offering providers the agility and flexibility to use it in last-mile fiber network applications, both above and below ground
- Protected from harsh conditions by CommScope’s Octopus gel sealing technology
- Agnostic to connectivity technologies: splice, connector, field-installable connector for agility and flexibility
- Identification plate for either QR code or customer logo
- QR code and CommScope cTrak® app for one-click access to all product information

## Product Classification

Regional Availability	Asia   EMEA   Latin America
Product Type	Single-ended, rectangular fiber closure
Product Brand	NOVUX™
Product Series	SRC50

## General Specifications

Cable Capacity, Drop	2 Flat 8.0 x 4.5 mm (0.30 x 0.17 in)   2 Round 1.2–8.0 mm (0.05–0.31 in)
Cable Ports Quantity, total	2 multi-out ports (4 cables)
Cable Sealing Type	Gel filled
Cable Termination Attachments, quantity	2
Closure Sealing Type	Hinged with latch
Closure Style	Single-ended
Color	Black
Mounting	Handhole   Partially buried   Pedestal   Wall/Pole Mount, mounting kit included
Network Area Type	Drop
Port Type	SC/APC
Port, quantity	2
Splicing Capacity, maximum	6
Splicing Capacity, Single Fusion, maximum	6

# SRC1-U3B2A1BC000

Splicing Type, Supported	Single fusion
Dimensions	
Height	267 mm   10.512 in
Width	87 mm   3.425 in
Depth	49 mm   1.929 in
Cable Entry Drop Port Diameter	8 mm   0.315 in
Material Specifications	
Material Type	Impact-resistant polymer
Optical Specifications	
Fiber Type	G.657.A1   G.657.A2   G.657.B3
Environmental Specifications	
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	Above ground   Below ground
Qualification Standards	IEC 60529, IP68 + 2 m waterhead   IEC 61753-1, category G
UV Resistance	UV stabilized
Water Resistance	Flash test valve at 2 psi (20 kPa)
Packaging and Weights	
Packaging quantity	1
Packaging Type	Box   Carton
Included Products	
NVX-CR-MC-RD-NN	– NOVUX™ Cable Termination Unit (CTU) for round cables with 4 to 6,2 mm diameter, metal clip