



SnapStak® Hanger for 1/2 in coaxial cable

Product Classification

Product Type	Hanger kit
Product Brand	SnapStak®
Ordering Note	CommScope® standard product in Asia Pacific CommScope® standard product in the United States and Canada

General Specifications

Cables per Hanger	1
Color	Silver
Hanger Type	Snap-in hanger
Mounting	3/4 in drilled cable ladder

Dimensions

Height	40.894 mm 1.61 in
Maximum Stack Height	3
Width	22.86 mm 0.9 in
Length	66.04 mm 2.6 in
Compatible Diameter, maximum	16.256 mm 0.64 in
Compatible Diameter, minimum	13.716 mm 0.54 in
Nominal Size	1/2 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

SSH-12

Material Type

Stainless steel

Mechanical Specifications

Vibration Survival

=4 hours at resonant frequency

Environmental Specifications

Operating Temperature

-40 °C to +85 °C (-40 °F to +185 °F)

Corrosion Resistance, minimum with no degradation

=500 hours in salt spray chamber

Environmental Strength Capability

Double cable weight

Packaging and Weights

Height, packed

15.2 cm | 5.984 in

Width, packed

10.4 cm | 4.094 in

Length, packed

9 cm | 3.543 in

Packaging quantity

10

Weight, gross

0.36 kg | 0.794 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



* Footnotes

Maximum Stack Height

Fiber, Hybrid, Power