

## Han 3A-AK (Kunstst. sw)



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 09 20 003 5450                                                                        |
| Specification      | Han 3A-AK (Kunstst. sw)                                                               |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09200035450">https://b2b.harting.com/09200035450</a> |

### Identification

|                             |                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------|
| Category                    | Accessories                                                                                        |
| Series of hoods/housings    | Han A <sup>®</sup>                                                                                 |
| Type of hood/housing        | Protection cover                                                                                   |
| Description of hood/housing | for bulkhead mounted housings<br>for surface mounted housings<br>Thermoplastic<br>With fixing cord |

### Version

|              |                         |
|--------------|-------------------------|
| Size         | 3 A                     |
| Locking type | Single locking lever    |
| Details      | for mounted male insert |

### Technical characteristics

|                                        |                                                    |
|----------------------------------------|----------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                                    |
| Degree of protection acc. to IEC 60529 | IP44<br>IP65 / IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                                      |

### Material properties

|                                           |                      |
|-------------------------------------------|----------------------|
| Material (hood/housing)                   | Polycarbonate (PC)   |
| Colour (hood/housing)                     | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0                  |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |                      |
|--------------------------------------|----------------------|
| RoHS                                 | compliant            |
| ELV status                           | compliant            |
| China RoHS                           | e                    |
| REACH Annex XVII substances          | Not contained        |
| REACH ANNEX XIV substances           | Not contained        |
| REACH SVHC substances                | Not contained        |
| California Proposition 65 substances | Yes                  |
| California Proposition 65 substances | Lead                 |
| Fire protection on railway vehicles  | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels   | R22 (HL 1-3)         |
|                                      | R23 (HL 1-3)         |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

## Commercial data

|                                |                                        |
|--------------------------------|----------------------------------------|
| Packaging size                 | 10                                     |
| Net weight                     | 5.68 g                                 |
| Country of origin              | Romania                                |
| European customs tariff number | 85389099                               |
| GTIN                           | 5713140039049                          |
| ETIM                           | EC002314                               |
| eCl@ss                         | 27440208 Cap for industrial connectors |