Product Specifications

COMMSCOPE®

Systimax Solutions

ZC12B3B0000-F010

InstaPATCH® ZERO Cord Cassette with twelve Category 6 U/UTP patch cords, dark gray jacket, tail length 10 feet

Configuration Specifications

ANSI/TIA Category	6
Cable Types	U/UTP (unshielded)
Jacket Color, copper	Dark gray
Interface Feature, copper connector A	Standard
Interface Feature, copper connector B	Standard
Interface, copper connector A	RJ45 plug
Interface, copper connector B	RJ45 plug
Port Quantity, copper	12

Dimensions

Tail Length	3.0 m | 10.0 ft
Connection Range, overhead	914.4 mm | 36.0 in
Depth	711.2 mm | 28.0 in
Height	289.6 mm | 11.4 in
Weight	9.07 kg | 20.00 lb
Width	43.7 mm | 1.7 in

Environmental Specifications

Safety Standard	CE | cETL | ETL

General Specifications

Brand	InstaPATCH® ZERO | SYSTIMAX®
Color	Black
Finish	Powder-coated, smooth
Ordering Note	Available in Mexico, Central America, and South America | Available in the United States and Canada
Package, quantity	1

Mechanical Specifications

Material Type	Plastic | Steel

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

©2013 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: April 23, 2012

ZC12B3B0000-F010

Included Products

860017029 | 1074E DG 4/24 RVAR (Product Component—not orderable) — GigaSPEED® XL 1074E Category 6 U/UTP Cable, non-plenum, dark gray jacket, 4 pair count, variable length, reel

©2013 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: April 23, 2012